



Overview

Lead time	Usually in Stock
-----------	------------------

General

Provided equipment	CD with software Smart UPS signalling RS-232 cable User manual USB cable
Performance multiplier	1
Number of tare power	45 W
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No
Size UPS version	Internetworking Server Telecom
UPS size	S
Value multiplier	1

Physical

Number of rack unit	0U
Colour	Black
Depth	54.4 cm
Height	43.2 cm
Mounting location	Front
Mounting preference	No preference
Net weight	50.92 kg
Mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	Yes
Width	19.6 cm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Input

Network frequency	50/60 Hz +/- 3 Hz auto-sensing
Plug standard	IEC 320 C20 Schuko CEE 7 / EU1-16P BS1363A British
Input voltage limits	151...302 V adjustable 160...286 V
Number of cables	1
Input voltage	230 V

Output

Rated power in W	1980 W
Maximum configurable power in W	1980 W
Harmonic distortion	Less than 5 % at full load
Output frequency	47...53 Hz for 50 Hz nominal sync to mains 57...63 Hz for 60 Hz nominal sync to mains
Crest factor	Up to 5 : 1
UPS type	Line interactive
Wave type	Sine wave
Nb of power socket outlets	8 IEC 320 C13 2 IEC Jumpers 1 IEC 320 C19
Curve equation	Efficiency
Curve load maximum	100 %
Curve X-axis maximum	100 %
Curve X-axis minimum	0 %
Curve X-axis title	Load
Curve X-axis units	Percentage
Curve Y-axis maximum	100 %
Curve Y-axis minimum	50 %
Curve Y-axis title	Efficiency
Curve Y-axis units	Percentage
Efficiency	95 % (full load)
Graph display	1
Output voltage	230 V
Maximum configurable power in VA	2200 VA
Rated power in VA	2200 VA
Transfer time	2 ms typical

Conformance

Product certifications	C-Tick CE GOST VDE
Standards	EN 50091-1 EN 50091-2

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-15...45 °C
Storage altitude	0.00...15240.00 m

Acoustic level	45 dBA
Heat dissipation	275 Btu/h
Show note OP temperature	No

Batteries & Runtime

Battery type	Lead-acid battery
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	3 h
Number of battery replacement quantity	1
Additional information	Configurable for 220 : 230 or 240 nominal output voltage
Liquid value	0
Battery curve	Z
Battery charger power	271 W rated
Battery power in VAH	816 VAh runtime
Battery life	3...5 year(s)
Extended runtime	0

Communications & Management

Free slots	1
Control panel	LED status display with load and battery bar-graphs and on line : on battery : replace battery : and overload indicators
Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays
Emergency power off	Optional

Surge Protection and Filtering

Surge energy rate	365 J
Noise suppression	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

Packing Units

Package 1 Weight	65 kg
Package 1 Height	70 cm
Package 1 width	38 cm
Package 1 Length	76 cm
Number of Units in Package 2	1
Number of Units in Package 3	9

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Optimized Energy Efficiency	Energy efficient product

Contractual warranty

Warranty	2 years repair or replace, optional on-site warranties available, optional extended warranties available
----------	--

SUA2200I is replaced by:



Smart-UPS SMT2200I

APC Smart-UPS 2200VA LCD 230V

Qty 1

Reason for Substitution: End of life | Substitution date: 15 June 2020 | Migration SPD
